

REFERENCES

- Zhi Ren A, A., Tashin, Satoshi Sasaki, Kouji Segawa and Yoichi Ando. (2011). Optimizing $\text{Bi}_{2-x}\text{Sb}_x\text{Te}_{3-y}\text{Se}_y$ solid solutions to approach the intrinsic topological insulator regime. *PHYSICAL REVIEW B* 84, 165311. doi: 10.1103/PhysRevB.84.165311
- Rowe, D. M. (2005). *Thermoelectrics handbook: macro to nano*: CRC press.
- Shelimova, L. E., Karpinskii, O. G., Zemskov, V. S., & Konstantinov, P. P. (2000). Structural and electrical properties of layered tetradymite-like compounds in the $\text{GeTe}-\text{Bi}_2\text{Te}_3$ and $\text{GeTe}-\text{Sb}_2\text{Te}_3$ systems. *Inorganic Materials*, 36(3), 235–242. doi: 10.1007/BF02757928
- Y. Feutelais, B., Lendre, N., Rodier and V., Agafonov. (1993). A study of the phases in the bismuth-telluride system. *J.Materials Research Bulletin*, 50, 591–596.
- D.Li, R.R., Sun and X.Y., Qin. (2011). Thermoelectric properties of p-type $(\text{Bi}_2\text{Te}_3)_x(\text{Sb}_2\text{Te}_3)_{1-x}$ prepared by spark plasma sintering. *Intermetallics* 19, 2002–2005. doi: 10.1016/j.intermet.2011.07.010
- L.Hu, T. Zhu, X.Liu, and X.Zhao. (2015). Point defect engineering of High-performance bismuth-telluride-based thermoelectric materials. *Materials, Adv. Funct. Mater* 24, 5211.
- B. Pouel, Q. Hao, Y. Ma, Y. Lan, A. Minnich, B. Yu, X. Yan, D. Wang, A. Muto, D. Vashaei, X. Chen, J. Liu, M. S. Dresselhaus, G. Chen, and Z. Ren. (2008). High-thermoelectric performance of nanostructured bismuth antimony telluride bulk alloy. *Science* 320, 634.
- W. Xie, X. Tang, Y. Yan, Q. Zhang, and T. M. Tritt. (2009). Unique nanostructures and enhanced thermoelectric performance of melt-spun BiSbTe alloys, 94 102111.
- S.I. Kim, K.H.Lee, H.A.Mun, H.S. Kim, S.W. Hwang, J.W. Roh, D.J. Yang, W.H. Shin, X.S. Li, Y.H. Lee, G.J. Snyder, and S.W. Kim. (2015). Densedislocation arrays embedded in grain boundaries for high-performance bulk thermoelectrics. *Science* 348, 109.

- Rowe, D.M. (2015). Thermoelectirc handbook: nacro to nano: CRC press.
- Tosawat Seetawan. (2015) Thermoelectrics Techanology: printed at 2. Publisher of Chulalongkorn college.
- Paiboon Kovitcharoenkul. (2008). Development of thermoelectric generatoor waste heat.
- Tosawat Seetawan. (2013) Thermoelectric Techanology: printed at 1. Publisher of Chulalongkorn college.
- Fergus, J.W. (2012). Oxid materials for high temperature thermoelectric energy conversion. *Journal of the European Ceramic Society* 32, 525–540.
- Dinesh K. Aswal, Ranita Basu and Ajay Singh. (2016). Key issuer in development of thermoelectric power generators: high figure of merit materials and their highly conducting interfaces with metallic interconnects. 144, 50–67
- Kim H, Han M-K, Yo C-H, Lee W and Kim S-J. (2012). Effects of Bi_2Te_3 nanoparticle inclusions on the microstructure and thermoelectric properteis of Bi_2Te_3 -based nanocomposites. *J. Electron Mater* 41, 3411–6.
- Culebras M, Uriol B and Gómez CM, Cantarero. (2015). A Controlling the thermoelectric properties of polymers: application to PEDOT and polypyrrole. *Phys Chem Chem Phys* 17, 15140–5.
- Antonenko AO, Charnaya EV, Nefedov DY, Podorozhkin DY, Uskov AV, Bugaev AS, Lee MK, Chang LJ, Naumow SV, Perevazchikove YA, Chistyakov VV, Marchenkova EB, Weber HW, Huang JCA, Marchenkova VV. (2017) NMR studies of single crystals of the topological insulator Bi_2Te_3 at low temperature. *Phys Solid state* 59, 855–9
- Luo B, Deng Y, Wang Y, Gao M, Zhu W, Hasim HT, García-Cañadas and J. Synergistic. (2016). Photovoltaic–thermoelectric effect in a nanostructured $\text{CdTe}/\text{Bi}_2\text{Te}_3$ heterojunction for hybrid energy harversting. *RSC Adv* 6, 114046.51.

- Guo W, Ma J, Zheng W. (2016). Bi₂Te₃ nanoflowers assemble of defective nanosheets with enhanced thermoelectric performance. *J. Alloy Compd* 659, 170–7.
- Cristina V. Manzano, Begoña Abad, , Miguel Muñoz Rojo, Yee Rui Koh, Stephen L. Hodson, Antonio M. Lopez Martinez, Xianfan XU, Ali Shakouri, Timothy D. Sands, Theodorian Borca-Tasciuc and Marisol Martin-Gonzalez. (2016). Anisotropic Effects on the thermoelectric properties of highly oriented electrodeposited Bi₂Te₃ films. *Sci. Rep.* 6 19129, doi: 10.1038/srep19129.
- Haynes, William M. (2011). CRC Handbook of chemistry and physics. CRC press. P.4.52. ISBN 1439855110.
- Guo W, Ma J and Zheng W. (2016). Bi₂Te₃ nanoflowers assembled of defective nanosheets with enhanced thermoelectric performance. *J. Alloy Compd* 659, 170–7.
- Chung D-Y, Hogan T, Brazis P, Rocci-Lane M, Kannewurf C and Bastea M. (2000). CsTi₄Te₆: a high-performance thermoelectric material for low-temperature application. *Science* 287, 1024–7.
- Jiang Q, Yan H, Khalid J, Ning H, Grasso S and Simpson K. (2014). Large ZT enhancement in hot forged nanostructured p-type Bi_{0.5}Sb_{1.5}Te₃ bulk alloys. *J. Mater Chem A*, 5785–90.
- Hu L-P, Zhu T-J, Wang Y-G, Xie H-H, Xu Z-J and Zhao X-B. (2016). Shifting up the optimum figure of merit of p-type bismuth telluride-based thermoelectric material for power generation by suppressing intrinsic conduction. *NPG Asia Mater* 88, 1–8. <http://dx.doi.org/10.1038/am.2013.86>
- Gaikwad M, Shevade D, Kadam A and Subham B. (2016). Review on thermoelectric refrigeration: materials and technology. *J Curr Eng Technol* 4, 67–71.
- Fergus, J.W. (2012). Oxide materials for high temperature thermoelectric energy conversion. *Journal of the European Ceramic Society* 32, 525–540.
- Tempsens. (2016). Temperature Hand Book. By four technocrats in 1976 at Udaipur.
- Arduino

- Yuan Yu, Bin Zhu, Zhan Wu, Zhong-yue Huang, Xiao-yu and Fang-qiu Zu. (2015). Enhancing the thermoelectric performance of free solidified p-type $\text{Bi}_{0.5}\text{Sb}_{1.5}\text{Te}_3$ alloy by manipulating its parent liquid state. *66*, 40–47
- Go-Eun and Il-Ho Kin. (2014). Preparation and Thermoelectric Properties of $\text{Bi}_2\text{Te}_3 - \text{Bi}_2\text{Se}_3$ Solid Solutions. *Journal of the Korean Physical Society*, Vol. 64, No. 10, May 2014, pp. 1416–1420
- L.P. Hu, X.H. Liu, H.H. Xie, J.J. Shen, T.J. Zhu and X.B. Zhao. (2012). Improving thermoelectric properties of n-type bismuth–telluride–based alloys by deformation–induced lattice defects and texture enhancement. *Acta Materialia*. *60*, 4431–4437
- Chan-Chieh Lin, Dianta Ginting, R.Lydia, Min Ho Lee, and Jong-Soo Rhyee. (2016). Thermoelectrc properties and extremely low lattice themal conductivity in p-type bismuth tellurides by Pb-doping and PbTe precipitation. *Journal of Alloy and Compounds* (2016)
- Qinghui Jiang, Junyou Yang, Jiwu Xin, Zhiwei Zhou, Dan Zhang and Haixue Yan. (2017). Carriers concentration tailoring and phonon scattering from n-type zinc oxid (ZnO) nanoinclusion in p-and n-type bismuth telluride (Bi_2Te_3): Leading to ulta kow thermal conductivity and excellent thermoelectric properties. *Journal of Alloys and Compounds* *694*, 864–868.
- Anil K. Bohra, Ranu Bhatt, Ajay Singh, Ranita Basu, Shovit Bhattacharya, K.N. Neshram, Sajid Ahmad, A.K. Debnath, A.K. Chauhan, Pramod Bhatt, Kunjal Shah, Ketan Bhotkar, Saloni Sharma, D.K. Aswal, K.P. Muthe and S.C. Hadkari. (2017). Tellurium–free thermoelectric: Improved thermoelectric performance of n-type Bi_2Se_3 having multiscale hierarchical architecture. *Energy Conversion and Management* *145*, 415–424.
- Hyunyong Cho, Jin Hee Kim, Song Yi Back, Kyunghan Ahn, Jong-Soo Rhyee and Su-Dong Park. (2017). Enhancement of thermoelectric properties in Cul-doped

- $\text{Bi}_2\text{Te}_{2.7}\text{Se}_{0.3}$ by hot-deformation. *Journal of Alloys and Compounds*. doi: 10.1016/j.jallcom.2017.10.016.
- Zhenxiang Yi, Xiaoping Liao and Hao Wu. (2015) Analysis and experiment of temperature effect on the thermoelectric power sensor. 224, 99–105.
- J. Kuchie and N.D. Love. (2014). Self powered wireless thermoelectric sensor. 47, 26–32.
- Yongming Shi, Yao Wang, Yuan Deng, Hongli Gao, Zhen Lin, Wei Zhu and Huihong Ye. (2014). A novel self-powered wireless temperature sensor based on thermoelectric generators. 80, 110–116.
- Shaowei Qing, Alireza Rezania, Lasse A. Rosendahl, Ali A. Enkeshafi and Xiaolong Gou. (2018). Characteristics and parametric analysis of a novel flexible ink-based thermoelectric generator for human body sensor. *Energy Conversion and Management* 156, 655–665.
- Huan Cheng, Yirui Du, Bijia Wang, Zhiping Mao, Hong Xu, Linping Zhang, Yi Zhong, Wan Jiang, Lianjun Wang and Xiaofeng Sui. (2018). Flexible Cellulose-based thermoelectric sponge towards wearable pressure sensor and energy harvesting. *Chemical Engineering Journal*, doi: <https://doi.org/10.1016/j.cej.2017.12.134>.
- J.Y. Yang, X.A. Fan, R.G. Chen, W. Zhu, S.Q. Bao and X.K. Duan. (2006). Bi_2Te_3 hexagonal nanoplates and thermoelectric properties of n-type Bi_2Te_3 nanocomposites. *J. Alloy and Compounds* 416. 270 – 273
- Yong Soo Lim, Won-Seon Seo, Byeong-Jun and Chang-Won Hwang. (2014). Preparation and thermoelectric properties of iodine-doped Bi_2Te_3 - Bi_2Se_3 solid solutions. *J. Korean Physical Society* 64. 1416 – 1420
- Xi'an Fan, Fan Yang, Zhenzhou Rong, Xinzhi Cai and Guangqiang Li. (2015). Lattice Thermal Conductivity Reduction Due to In Situ-Generated Nano-Phase in $\text{Bi}_{0.4}\text{Sb}_{1.6}\text{Te}_3$ Alloys by Microwave-Activated Hot Pressing. *J. Ceramic International* 41. 6817 – 6823

- Yun Min Kim, R. Lydia, Jin Hee Kim, Chan-Chieh Lin and Kyughan Ahn. (2017). Enhancement of thermoelectric properties in liquid-phase sintered Te-excess bismuth antimony tellurides prepared by hot press sintering. *J. Acta Materialia* 135. 297 – 303
- Overview, D. D. (2013). Advanced X-ray Diffraction System for Materials Research Applications.
- Oumaima Gharbi. (2016). In-situ investigation of elemental corrosion reactions during the surface treatment of Al-Cu and Al-Cu-Li alloys.
- Yun Min Kim, R. Lydia, Jin Hee Kim, Chan-Chieh Lin and Kyughan Ahn. (2017). Enhancement of thermoelectric properties in liquid-phase sintered Te-excess bismuth antimony tellurides prepared by hot press sintering. *J. Acta Materialia* 135. 297 – 303
- H.M. Ismail, M.A. Khattak, M.N. Tamin, M.S. Khan, N.Iqbal, S. Kazi, S. Badshah and R. U. Khan. (2016). Energy Absorption Ability of Thin-Walled Square Hollow Section of Low Carbon Sheet Metals under Quasi-Static Axial Compression
- P. Giannozzi, S. Baroni, N. Bonini, M. Calandra, R. Car, C. Cavazzoni, D. Ceresoli, G. L. Chiarotti, M. Cococcioni, I. Dabo, A. D. Corso, S. de Gironcoli, S. Fabris, G. Fratesi, R. Gebauer, U. Gerstmann, C. Gougoussis, A. Kokalj, M. Lazzeri, L. Martin-Samos, N. Marzari, F. Mauri, R. Mazzarello, S. Paolini, A. Pasquarello, L. Paulatto, C. Sbraccia, S. Scandolo, G. Sclauzero, A. P. Seitsonen, A. Smogunov, P. Umari and R. M. Wentzcovitch. (2009). QUANTUM ESPRESSO: a modular and open-source software project for quantum simulations of materials. *J. Physics Condensed Matter*. 21. 395502
- J. P. Perdew, K. Burke, M. Ernzerhof. (1996). Generalized Gradient Approximation Made Simple. *J. Phys Rev Lett.* 77. 3865

- T.J. Scheidemantel, C. Ambrosch-Draxl, T. Thonhauser, J.V. Badding and J.O. Sofo. (2003). Transport coefficients from first-principles calculations. *J. Phys Rev B.* 68. 125210
- S. Ruamruk, K. Singsoog, P. Pilasuta, S. Paengson, W. Namhongsa, M. Rittiruam and T. Seetawan. (2018). Electronic structure and thermoelectric properties of $\text{Bi}_{2-x}\text{Sb}_x\text{Te}_3$ ($x = 0, 0.33, 0.67$) by first principle calculation. *J. Materials Today: Proceedings* pages 14150–14154
- J.Y. Yang, X.A. Fan, R.G. Chen, W. Zhu, S.Q. Bao and X.K. Duan. (2006). Bi_2Te_3 hexagonal nanoplates and thermoelectric properties of n-type Bi_2Te_3 nanocomposites. *J. Alloy and Compounds* 416. 270 – 273
- Yong Soo Lim, Won-Seon Seo, Byeong-Jun and Chang-Won Hwang. (2014). Preparation and thermoelectric properties of iodine-doped $\text{Bi}_2\text{Te}_3-\text{Bi}_2\text{Se}_3$ solid solutions. *J. Korean Physical Society* 64. 1416 – 1420
- Xi an Fan, Fan Yang, Zhenzhou Rong, Xinzhai Cai and Guangqiang Li. (2015). Lattice Thermal Conductivity Reduction Due to In Situ-Generated Nano-Phase in $\text{Bi}_{0.4}\text{Sb}_{1.6}\text{Te}_3$ Alloys by Microwave-Activated Hot Pressing. *J. Ceramic International* 41. 6817 – 6823
- Yun Min Kim, R. Lydia, Jin Hee Kim, Chan-Chieh Lin and Kyughan Ahn. (2017). Enhancement of thermoelectric properties in liquid-phase sintered Te-excess bismuth antimony tellurides prepared by hot press sintering. *J. Acta Materialia* 135. 297 – 303
- Natl. Bur. Stand. (U. S.) (1964). Standard X-ray Diffraction Powder Patterns Monogr. 25 3, 16 (1964).
- Ritter, J., National Inst. of Standards and Technology, Gaithersburg, MD, USA. Private Communication (1997).

- Go-Eun Lee and Il-Ho Kim. (2014). Preparation and Thermoelectric Properties of Bi_2Te_3 – Bi_2Se_3 Solid Solution. *Journal of the Korean Physical Society*, Vol. 64, No. 10, May 2014, pp. 1416~1420
- YunMin Kim, R. Lydia, Jin-Hee Kim, Chan-Chieh Lin, Kyunghan Ahn and Jong-Soo Rhyee. (2017). Enhancement of thermoelectric properties in liquid-phase sintered Te-excess Bismuth Antimony Tellurides prepared by hot press sintering. *Acta Materialia* 135
- S. Ruamruk, K. Singsoog, P. Pilasuta, S. Paengson, W. Namhongsa, M. Rittiruam and T. Seetawan. (2018). Electronic structure and thermoelectric properties of $\text{Bi}_{2-x}\text{Sb}_x\text{Te}_3$ ($x = 0, 0.33, 0.67$) by first principle calculation. *Materials Today: Proceedings* 5 (2018) 14150–14154
- P. Giannozzi, S. Baroni and R. M. Wentzcovitch (2011). Electronic structure and transport anisotropy of Bi_2Te_3 and Sb_2Te_3 . *J. Phys. Rev. B* 84, 165208
- J. P. Perdew, K. Burke and M. Ernzerhof. (1996). Generalized Gradient Approximation Made Simple. *J. Phys Rev Lett.* 77, 3865.
- K.H.M. Georg and D. J. Singh, (2006). BoltzTraP. A code for calculating band-structure dependent quantities. *J. Comput Phys Commun.* 175 (2006) 67–71.
- T.J. Scheidemantel, C. Ambrosch-Draxl, T. Thonhauser, J.V. Badding and J.O. Sofo. (2003) Transport coefficients from first-principles calculations *J. Phys Rev B*. 68 125210.